


Model: H-AA1800M





★ Specifications

Nominal Voltage	1.2 V	Final Discharge Voltage	1.0 V
Dimension of Production (with tube)	D(Diameter)	14.5 ^{+0.0} _{-0.7} mm	
	C(Top)	8.0 ± 0.2 mm	
	H(Height)	50.0 ^{+0.0} _{-1.0} mm	
Capacity	Nominal	1800 mAh (minimum at 0.1C/0.2)	
	Typical	1620 mAh (minimum at 0.1C/1C)	
Charging	Standard	0.1C (180mA) for 14~16 hrs	
	High Rate	0.5C (900 mA) for approx. 2.25 hrs	
Temperature Range for Operation (Humidity: Max 85%)	Standard Charge	0 ~ +45 °C	
	Rapid Charge	+10 ~ +45 °C	
	Discharge	-20 ~ +60 °C	
	Storage	-20 ~ +55 °C (less than 1 month)	
-20 ~ +35 °C (less than 1 year)			
Internal Impedance at 1000Hz	Approx. 20 mΩ at after charge		
Weight	27.0 g	Service Life	≥ 500 cycles


★ Construction




★ Typical Characteristics



Typical Effect of Cell Discharge Temperature on Voltage-MPV



Typical Effect of Cell Charge Temperature on Actual Capacity



*Weight , Service Life and Internal Impedance are for reference.